BOPP FIM POLYPROPYLENE SEALABLE BY BOTH SIDES.								
DESCRIPTION								
The film presents thermal sealability on both sides. This film contains an immigration package slip and antistatic additive that provides excellent machinability in all kinds of automatic packing. The untreated side offers a wide range of sealing. The surface treatment is on the outside of the coil. APLICATIONS Designed to be used in a variety of conversion processes and packaging of all types of industrial and food products in casings or laminations. Meets FDA regulations for direct food contact. Its properties allow it to be used sealants in numerous applications with sealed end flap or overlap in vertical or horizontal automatic packing.								
Standar Dimentions								
Thickness (um)	Weight (g/m2)	Wide (mm)	center carton	550mm External Diameter		760mm External Diameter		
				length(m)	weight(Kg/cm)	length(m)	weight(Kg/cm)	Treated side
15	13.6			13.900		27.800		
17.5	15.8			11.900		23.800		
20	18.1	400		10.300		20.600		
25	22.6	to	3" to 6"	8.250	1.89	16.500	3.77	External
30	27.2	2000		6.900		13.800		
35	31.7			5.900		11.800		
40	36.2			5.150		10.300		
50	45.3			4.150		8.300		

Asia Pacific Industry Group Co., Limited
http://www.boppfilmsales.com
Skype:asiapacificsale
Wechat/whatsapp/mobile:86 18919654871
Anhui Eastern Communication Chemicals
http://www.boppfilmsale.com

地址 ADD.: No.3399, Luzhou Ave., Baohe Dist., Hefei, Anhui 230051, China | 安徽省合肥市包河区庐州大道3399号
传真 Fax: +0086-551-64683490 营业执照注册号 Business License Reg. No.: 91340100575703313N
海关注册编码 Customs Reg. Code: 3401961393

ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

Hoja1

MAIN CHARACTERISTICS Flexibility of use
Excellent antistatic properties
Magnific flatness and dimensional stability
One side treated for applying dyes or additives
outer surface treated to application of ink or additives
A wide sealing range

Standar Dimentions

Thickness (um)	Weight (g/m2)	Wide (mm)	center carton	550mm External Diameter		760mm External Diameter		
				length(m)	weight(Kg/cm)	length(m)	weight(Kg/cm)	Treated side
15	13.6	400 to 2000	3" to 6"	13.900	1.89	27.800	3.77	External
17.5	15.8			11.900		23.800		
20	18.1			10.300		20.600		
25	22.6			8.250		16.500		
30	27.2			6.900		13.800		
35	31.7			5.900		11.800		
40	36.2			5.150		10.300		
50	45.3			4.150		8.300		

Asia Pacific Industry Group Co., Limited
http://www.boppfilmsales.com
Skype: asiapacificsales
Wechat/whatsapp/mobile:86-18919654871
Anhui Eastern Communication Chemicals
http://www.boppfilmsales.com

Página 2